

FLUSH MOUNT LIGHTS

available in: 



FEATURES

- Available in LED or halogen versions.
- Highly polished flange included.
- Durable polycarbonate parts.
- All mounting hardware included.
- LED versions available in red, blue, or amber.
- Halogen versions available in red, blue, amber, or clear.
- Five year warranty on LED models.

Federal Signal's line of flush mount lights combine attractive design with effective warning power. Models are available in LED or halogen. Durable polycarbonate parts and a thick gasket extend service life.

GL1F LED versions contain 60 LEDs and have a built in flasher with eight patterns. Up to six units can be synchronized together, no additional flasher is required.

When illuminated the GH1F models feature 35-watt halogen bulbs that draw 2.5 amps. GH3F models feature 55-watt halogen bulbs that draw 4.8 amps. Using an FA3-SC flasher with either model creates a 90 FPM warning pattern.

Perfect for midship lighting, Federal Signal's flush mount lights aesthetically complement FIRERAY™ and MODLED™ LED perimeter lights.

When GL1F and GH1F models are installed in an area not protected by the vehicle's interior, model GWM1 back plates may be purchased to protect the light from debris.

GH halogen models require body panel cutouts and feature a unique flange for flush mount appearance. GL1F models are surface mounted and require no body panel cutout.

HOW TO ORDER

SPECIFY A MODEL

Mounting hardware included.

- GH1F** (1) flush mount halogen lamp with flange, small
- GH3F** (1) flush mount halogen lamp with flange, large
- GL1F** (1) flush mount LED with flange, small

SPECIFY COLOR

- GH1F/GH3F** Red, blue, amber, or clear
- GL1F** Red, blue, or amber

SPECIFY ACCESSORIES AND OPTIONAL EQUIPMENT

- GWM1** Optional back plate for small models
- FA3-SC** Alternating flasher, 90 FPM, flashes up to six GH1F or four GH3F lamps



Both LED and halogen versions rest flush with the vehicle surface.

	GL1F	GH1F	GH3F
Specification			
Light Source	60 LEDs	35W halogen bulb	55W halogen bulb
Current Draw @ 12.8 VDC	Red - 0.90 amps Blue - 1.10 amps Amber - 0.90 amps	2.5 amps	4.8 amps
Input Voltage	12.8 VDC	12.8 VDC	12.8 VDC
Physical Specifications			
Height	3.6 in (9.3 cm)	3.6 in (9.3 cm)	1.4 in (10.4 cm)
Width	4.9 in (12.4 cm)	4.9 in (12.4 cm)	7.0 in (17.8 cm)
Depth	1.8 in (4.6 cm)	3.0 in (7.68 cm)	3.4 in (8.7 cm)
Ship Weight			
	1.0 lb (0.05 kg)	1.0 lb (0.05 kg)	1.0 lb (0.05 kg)